

Front**Back**

Model	133-0669
Product	4 Port Gigabit PoE Network Extender
PoE Input port	Supports 1/2(+), 3/6(-); 4/5(+), 7/8(-) MAX Input Power 90W
PoE Output port	Supports IEEE802.3af/at MAX Output Power 30W
Power	Default:No power
Watt	Standby Power Consumption: ≤5W; Full-load Power Consumption: ≤90W;
DC In	As Network Extender: DC9-57V MAX 0.5A As PoE Network Extender: DC37-57V MAX 0.5A
Function	N:(Standard Normal) V:(Port Isolation)
LED Indicator	Power:Power LED Vlan:(Port isolation LED) Port:(Green=Link LED+Orange=PoE LED)
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab1000BASE-T IEEE 802.3x IEEE 802.3af/at
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	12Gbps
Packet Forwarding	7.2Mpps
MAC Address	2K
Buffer	2.5M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)
Operating Temperature/Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	140mm*80mm*28mm; 215mm*175mm*45mm
N.W/G.W (kg)	0.3kg/0.4kg
Installation	Desktop
Lightning protection level	3KV 8/20us; IP30
Certificate	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)