



## Product Overview



20117399 is an industrial grade Unmanaged PoE Switch. 20117399 has 8\* 10/100/1000Mbps adaptive RJ45 ports and 2\*1000Mbps SFP fiber module slots. Ports 1-8 RJ45 support PoE power supply, with a maximum of 30W for each port. Each RJ45 port supports MDI/MDIX automatic rollover and wire speed forwarding.

The device adopts no fan, low power consumption design, has the advantages of easy to use, compact and beautiful and simple installation. 20117399 is designed to meet Ethernet standards, with lightning protection, static protection mechanism, operating temperature range of 40°C to 75°C, stable performance, safety and reliability, can be widely used in intelligent transportation, telecommunications, security, financial securities, customs and other broadband data transmission fields.

## Product Features

- Complies with IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x standards;
- RJ45 Supports automatic port flip (Auto MDI/MDIX);
- Automatic detection of PD devices;
- Port power priority is supported to ensure continuous power supply for key nodes on the network;
- Supports IEEE802.3x full-duplex flow control and Backpressure half-duplex flow control;
- No fan, full aluminum alloy high energy roof heat conduction tank;
- Panel indicators monitor working status and assist in fault analysis;
- Perfect security mechanism;
- Support VLAN and CCTV function;
- Wire speed forwarding, intelligent recognition;
- Data exchange adopts store-and-forward mode;
- Operating temperature: -40°C~75°C.

## Product Specifications

### Hardware Specification

Model	20117399
Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE802.3af, IEEE802.3at
Interface	8*10/100/1000Mbps RJ45 Ports 2*1000Mbps SFP Slots
Indicator	PWR, LNK/ACT, PoE
Network Media	10BASE-T: UTP category 3, 4, 5 cable( $\leq 100\text{m}$ ) 100BASE-TX: UTP category 5, 5e cable( $\leq 100\text{m}$ ) 1000BASE-T: UTP category 5e, 5 cable( $\leq 100\text{m}$ ) 1000BASE-X: MMF, SMF
MAC Address Table	4K, Auto-learning, Auto-aging
Jumbo Frame	9216Bytes
Packet Buffer	1.5Mbit
Transfer Mode	Store-and-forward
Packet Forward Speed	14.88Mpps
Switching Capacity	20Gbps
Dimensions(L*W*H)	145*109*62mm
Fan Quantity	Fanless
Power Supply	200W
PoE Budget	185W
PoE Port	Port1~8
PoE Power On RJ45	Mode A 1/2(-), 3/6(+)
PoE Power Output	30W(MAX)
Green Energy Saving	IEEE 802.3az
Input Power Supply	DC: 48-57V
Operating Temperature	-40°C ~ 75 °C
Storage Temperature	-40 °C ~ 80 °C
Operating Humidity	5% ~ 95% non-condensing
Storage Humidity	0% ~ 95% non-condensing
Surge Protection	Differential mode $\pm 2\text{KV}$ Common mode $\pm 4\text{KV}$
MTBF	>100000 hour
Electrostatic Standard	Contact $\pm 6\text{KV}$ , Air $\pm 8\text{KV}$

## Ordering Information

Model	Product Information
20117399	8-Port Gigabit+2G SFP Industrial PoE Switch

The logo for DIREKTRONIK is displayed in a bold, italicized, sans-serif font. The letters are white with a thick red outline. The 'D' is particularly large and stylized, with the 'I' and 'R' following its lead in size and style. The 'E' is smaller, and the 'K' is also stylized. The 'T' is tall and narrow, and the 'R' is wide and bold. The 'O' is a simple circle, and the 'N' is tall and narrow. The 'I' and 'K' are also tall and narrow. The 'E' is smaller. The 'T' is tall and narrow. The 'R' is wide and bold. The 'O' is a simple circle. The 'N' is tall and narrow. The 'I' and 'K' are also tall and narrow.

**DIREKTRONIK**

Direktronik AB tel. 08-52 400 700 [www.direktronik.se](http://www.direktronik.se)