

Ethernet 10Base-2/T Converter

● Description:

MFICO's 10Base-2/T Converter is designed to connect your existing Thin Ethernet adapter card or Thin Ethernet Network to a 10Base-T UTP network. This converter repeats signals from Thin Ethernet for transmission over Unshielded Twisted-Pair (UTP) cable to a 10Base-T hub.

● Specification:

| | |
|-----------------|--|
| Interface: | 1xRJ-45 Jack from (Hub/station) select switch 1xBNC socket to 10 Base-2 100 M max. per UTP cables |
| Cable length: | 185 M max. per Thin Ethernet |
| External Power: | Input 110V or 220V AC Output 9V DC, 1 Amp |
| Temperature: | 0 to 55C (standard operating) |
| Humidity: | 10 to 90% (non-condensing) |
| Standard: | IEEE 802.3 10Base-T/10Base-2 |
| EMI: | Meets FCC Class A Subpart B of Part 15 Requirement |
| Technique: | Baseband |
| Lan Expansion: | Twisted Pair expand upon to 4 level Thinnet up to 30 Hubs |
| Dimensions: | 0.79" (H) x 2.17" (W) x 4.09" (D) |
| Topology: | Star |
| Protocol: | CSMA/CD |

● Order Information:

MF-607 Ethernet 10Base-2/T Converter



Ming Fortune Industry Co., Ltd.

MFICO NETWORK TOTAL SOLUTION



*TEL:886-2-22286879*FAX:886-2-2228-6878*HTTP://www.mfico.com.tw*E-MAIL:mfico@ms3.hinet.net