

5G Dongle

UF31

DIREKTRONIK

Dataprodukter utöver det vanliga



UF31 is a high-performance 5G modem for 5G wireless networking applications. It supports 5G NSA&SA, 4G LTE and 3G networks from telecom service providers of most countries in the world. The USB type-C port and Ethernet port are adopted to provide high-speed internet access for field devices.

With a compact size and industrial design, UF31 is easy to carry out or embed to any equipment, which is particularly suitable for smart offices, video surveillance, digital media implementations, industrial automation, traffic applications, robots and so on.

◆ Features

- Support global 5G NSA&SA/4G LTE/WCDMA network, enables up to 2.5 Gbps download speeds
- Plug and play, provide lightning transmission via Gigabit Ethernet port or USB 3.0
- Embeds hardware watchdog to automatically recover from various failure, ensure highest level of availability
- Wide operating temperature range from -20°C to 50°C and industrial design for harsh environment
- USB or DC power supply optional
- Easy to deploy anywhere with compact size, suit for embedded installation

- Iptables firewall and VPN tunnels to ensure security data transmission
- WEB GUI and CLI enable the admin to achieve simple management and quick configuration among a large quantity of devices
- DeviceHub provides remote monitoring, bulk configuration, and centralized management

◆ Specifications

| Hardware System | |
|---------------------------|--|
| CPU | Quad-core ARM Cortex-A55, 2 GHz |
| Memory | 1 GB LPDDR4X RAM and 1 GB NAND Flash |
| Cellular Interface | |
| Network | 5G NR SA&NSA/4G LTE/WCDMA |
| Frequency | 5G Sub-6: N1/N3/N5/N7/N8/N20/N28/N38/N40/N41/N77/N78/N79 LTE FDD: B1/B3/B5/B7/B8/B18/B19/B20/B28/B32 LTE TDD: B38/B40/B41/B42/B43/B46 WCDMA: B1/B5/B8 |
| Antenna Connector | 4 × 50 Ω SMA Connectors (Center PIN: SMA Female) |
| SIM Slot | 1 (Micro SIM-3FF) |
| Ethernet Interface | |
| Numbers | 1 × 10/100/1000 Mbps LAN Port |
| Mode | Full or Half Duplex (Auto-Sensing) |
| GNSS | |
| Antenna Connector | 1 × 50 Ω SMA Connector (Center PIN: SMA Female) |
| Technology | GPS/GLONASS/Beidou/Galileo/QZSS |
| Others | |
| USB | 1 × USB 3.0 (Type-C) for Power Supply, Network Supply and Debug |
| Reset Button | 1 × RESET (Internal) |
| LED Indicators | 1 × STATUS, 1 × Cellular Network |
| Built-in | Watchdog, Timer |
| Software | |
| Network Protocols | IPv4/IPv6, TCP, UDP, DHCPv4/DHCPv6, HTTP, HTTPS, DNS, ARP, Telnet, SSH, etc. |
| Security ¹ | Access Control, Port Mapping, Custom Rules |

¹ Under development

Management Web, CLI, DeviceHub

Power Supply and Power Consumption

Power Connector 2-pin 3.5 mm Terminal Block

Power Input 1. 5-24 VDC, with Surge-Protection and Reverse Polarity Protection
2. 5V/3A by USB Type-C Port

Power Consumption Typical 3.9 W

Physical Characteristics

Ingress Protection IP30

Housing & Color Metal, Black

Dimension 90 x 72 x 15 mm (3.54 x 2.83 x 0.59 in)

Installation Desktop, Wall Mounting, DIN Rail Mounting

Environmental

Operating
Temperature -20°C to +50°C (-4°F to +122°F)

Storage
Temperature -40°C to +85°C (-40°F to +185°F)

Ethernet Isolation 1.5 kV RMS

Relative Humidity 0% to 95% (Non-condensing) at 25°C/77°F

The logo for DIREKTRONIK features the brand name in a bold, italicized, sans-serif font. The letters are white with a thick red outline, set against a yellow background that curves upwards from the bottom of the page.