

PDU Technology Specification

Date: 12/08/2022

NO.:

Customer	Direktronik	RoHS	Yes
Product Name	Designated Power Distribution Unit for Cabinet	Customer's Code	
Part Number	116-8228	Picture Code	
No.	Item	Detailed Description	
1	Product Series	AUE2211	
2	Socket Type	DIN49440 16A Socket[30];	
3	Socket Quantity	30	
4	Power Input	Left end single input	
5	Bracket Install	Inverse installation	
6	Cable with plug	IEC60309 plug (32A 2P+E)	
7	Control Function	No controlling function	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3 x 6.0 mm ² x 3M	
11	Product Size	L x W x H = 1568 x 56 x 44.4 mm	
12	Mounting Length	1547 mm	
13	Case Length	1515 mm	
14	PDU Exponent	1.997	
15	Fittings	2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut,	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	116-8228
		Rating voltage	250VAC 50/60Hz
		Rating Current	32A
		Max. Current	
		Max. Power	8000W
		Safety Authentication	CE
		Logo	RoHS
	Producer		
No.	Add-In		
1	Socket assemble	No	
2	Interior Connection Wire	2.5 mm ² (14AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp(19)	
5	Module Assemble (from left to right)	Pls refer to the drawing	

Preview



IEC60309 plug (32A 2P+E)

DIMENSION AND TOLERANCES (Unit: mm)			SHENZHEN CLEVER ELECTRONIC CO.,LTD	
Length: 1568	Mounting length: 1547		Customer	Direktronik
Width: 56	Case length: 1515		Product name	Designated Power Distribution Unit for Cabinet
Height: 44.4	case tolerance: ± 1.0		Part number	116-8228
	SIGN	DATE	Customer's code	
DRAWN	Linda	12/08/2022	Drawing number	
CHK'D			Edition number	
APP'D				