

SPDU Specification

Date: 20211207

No:004

Customer			
Product Name	Part No.		
SPDU	20110290		
Technical Specification			
Input	Input Plug	IEC60309 16A (3P+N+E) plug	
	Rating voltage	380VAC 50/60Hz	
	Rating current	3x16A	
	Max. power	3x4000W	
	Cable specification	5x2.5mm ² x3M	
Output	Outlet standard	IEC 320 C13 sockets [21]	
	Rating output voltage	250VAC	
	Rating current	16A	
	Digital ammeter	<input checked="" type="checkbox"/> LED <input type="checkbox"/> LCD	
Interior connection wire	<input type="checkbox"/> 16AWG <input checked="" type="checkbox"/> 14AWG <input type="checkbox"/> 12AWG <input type="checkbox"/> other		
Product size	L×W×H = 1649×44.4×66.50mm	Color	Black
Product label	Logo		
	Product name	Sequential Controlling Power Distribution Unit	
	Specification model	20110290	
	Voltage/current	380VAC 3x16A	
	Safety certification	CE	
	RoHS	RoHS	
Main function	Parameter	Remark	
Outlet group sequential power on/off	The outlets sequentially power on/off group by group (2 sockets or 3 sockets in one group) each phase with 3 groups, power up interval time is 4s.		
Product drawing			

