

## Gigabit PoE Splitter

### 1. INPUT :

- 1.1 Input Voltage: DC40V to DC60V NORMAL=56V
- 1.2 Under Voltage Lockout: DC 31 ~ 32V Stare Voltage =-33V ~ 35.5V

### 2. OUTPUT :

#### 2.1 Output Voltage & Current:

Model	
OUTPUT	+12V
Max. load	2.1A
Power	25W Max
Min. Load	0.1A
Load reg. %	5%
Line reg. %	1%
Ripple %(1)	1%
Noise %(1)	5%

TOTAL POWER : 25W

Note 1: Ripple & Noise bandwidth is from DC to 20Mhz. Terminated With a 47uF Capacitor and 0.1uf MPE Capacitor of Proper Polarity.

### 3. EFFICIENCY : 86% min @-48Vin dc

### 4. PROTECTION

#### 4.1 Short Circuit Protection

output Short GND Terminal will not damage the Power Supply and will Auto-Reset.

Over Load Protection is auto-recover.

#### 4.2 Operation frequency is 150KHZ

#### 4.3 Isolation Voltage : 1500Vdc

#### 4.4 Isolation Resistance :100M ohms (min)

#### 4.5 Identify Resistance : 25K ohms

#### 4.6 Maximum Capacitive Load : 470UF (24V = 100UF)

#### 4.7 Green LED indicates work as 802.3at Model.

RED LED indicates work as 802.3af Model



## 5. GENERAL DESCRIPTION

- 5.1 Operation Temperature: -40 - +70C  
 5.2 Storage Temperature: -40 - +85C  
 5.3 Operation Humidity: 5% - 90% non-condensing  
 5.4 Cooling: Free air cooling  
 5.5 SIZE : 85\*78\*36 (L\*W\*H)m/m (included bracket)  
 5.6 DC Power Plug: 2.1Φ (or 2.5Φ)/ 5.5Φ, L= 12+/-0.5mm, 180 degree  
 Polarity : inside (+), outside (-)

## 6. CONNECTORS & PINOUT DEFINITION:

### 6.1 Power-Hub RJ45 Input Socket (per channel) data & Power-Connected to DTE

RJ-45 Input (Data & Power)		
Pin	Symbol	Description
1	BI_DA+, Vin A+/-	Data Pair A+, Feeding power A+/-
2	BI_DA-, Vin A+/-	Data Pair A-, Feeding power A+/-
3	BI_DB+, Vin A+/-	Data Pair B+, Feeding power A+/-
4	BI_DC+, Vin B+/-	Data Pair C+, Feeding power B+/-
5	BI_DC-, Vin B+/-	Data Pair C-, Feeding power B+/-
6	BI_DB-, Vin A+/-	Data Pair B-, Feeding power A+/-
7	BI_DD+, Vin B+/-	Data Pair D+, Feeding power B+/-
8	BI_DD-, Vin B+/-	Data Pair D-, Feeding power B+/-
9	Shield	Connector shielding

### 6.2 Power Output & Data -Connected to DTE

RJ-45 Output (only Data)		
Pin	Symbol	Description
1	BI_DA+	Data Pair A+
2	BI_DA-	Data Pair A-
3	BI_DB+	Data Pair B+
4	BI_DC+	Data Pair C+
5	BI_DC-	Data Pair C-
6	BI_DB-	Data Pair B-
7	BI_DD+	Data Pair D+
8	BI_DD-	Data Pair D-
9	Shield	Connector shielding

Note : 1. the model is isolated design, the output +/- or input +/- can be shorted to ground (FG).

- 7. E M I      Meet FCC Class B Radiation standard  
                  Meet EN55032 Class B Radiation standard

