



RANGE SPECIFICATIONS / ESPECIFICACIONES DE LA GAMA						
Item Artículo	N.Conductors Nº Conductores	Stranding Ø Formación	Insulation OD Ø Exterior	Jacket OD Ø Exterior	Resistance Resistencia	m/Spool m/Bobina
MC-215	2 x 1,50 mm ²	12 x 7 x 0,15 mm	2,90 mm	7,80 mm	31 Ω/km	100
MC-225	2 x 2,50 mm ²	20 x 7 x 0,15 mm	3,50 mm	9,00 mm	19 Ω/km	100

COMMON SPECIFICATIONS / ESPECIFICACIONES COMUNES	
Conductor Material / Material Conductor	CCA
Insulation Material / Material Cubierta	Flame Retardant PVC
Color Insulation / Color Aislantes	Red - Black / Rojo - Negro
Color Jacket / Color Cubierta	Black / Negro
Cable Printing / Marcaje	MC-215 Master Cable 2X1,5mm ² LOUDSPEAKER CABLE MC-225 Master Cable 2X2,5mm ² LOUDSPEAKER CABLE
Color Printing / Color Marcaje	White (Ral 9010) / Blanco
Type Packing / Tipo Presentación	Cardboard Reel or Wooden Spool / Bobina de Cartón o Bobina de Madera
Max. Rate Voltage / Tensión Nominal	AC / CA 49 v
Temp. Range / Temp.Servicio	-15 + 70 °C