

## 20117364 RG 214 U Marine

Trippelshielded  
50Ω  
SHF1  
DNV / ABS


### Application

Coaxial cable for ship and other marine environments with Extra screen for excellent EMC properties. For for VHF/UHF equipment. MIL 17-C/75.



### Construction

Conductor	Stranded Silvercoated Cu 7 x 0,75 [mm]
Dielectricum	Low density PE 7,25 ± 0,18 [mm]
Screen	Al - polyester tape 100 [% optical coverage]
Screen	Silvercoated Cu braid 94 [% optical coverage]
Screen 2	Silvercoated Cu braid 98 [% optical coverage]
Jacket	Black SHF1
O.D.	10.8 ± 0.18 [mm]
Weight	206 [kg/km]



### Specifications

Operating temperature normal	-40 – +70 [°C]
Characteristic impedance	50±2 [Ω]
Braid Resistance	4.2 [Ω/km]
Conductor resistance	6 [Ω/km]
Test voltage	5.5 [kV]
Capacitance	100 [pF/m]
Min. bending radius	15 [x outer diam]



SE

**Direktronik AB** | Box 234, 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn  
Telefon 08 52 400 700 | Fax | Epost info@direktronik.se | Org.nr 556281-9663 | Bankgiro 922-0179



NO

**NEXLAN AS** | Kokstadflaten 19 B, 5257 Kokstad | Besöksadresse Kokstadflaten 19 B 5257 Kokstad  
Telefon 55 50 91 50 | Fax | E-post info@direktronik.no | Org.nr 986767215MVA | Bankgiro 36285556559

## Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1 & IEC 60754-2
Design and testing standards	IEC 60096-0-1 Ed 3
Flame resistance	IEC 60332-3-22 Cat.A
Flame retardant	IEC 60332-1
Smoke emission	IEC 61034-2
UV-resistant	UL 1581, ISO 4892
Certification	DNV / ABS

Available with MUD resistance



## Attenuation

Frequency (MHz)	Attenuation Max. (dB/100m)
5	1,1
10	1,5
50	3,8
100	5,4
200	7,9
300	9,9
500	12,9
600	14,5
800	17,2
1000	19,6
1350	23,5
1500	24,8
1750	27,4
2150	30,9
2250	31,8
2500	34,0
2750	36,0
3000	37,6
5500	55



SE



NO

**Direktronik AB** | Box 234, 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn  
Telefon 08 52 400 700 | Fax | Epost [info@direktronik.se](mailto:info@direktronik.se) | Org.nr 556281-9663 | Bankgiro 922-0179

**NEXLAN AS** | Kokstadflaten 19 B, 5257 Kokstad | Besöksadresse Kokstadflaten 19 B 5257 Kokstad  
Telefon 55 50 91 50 | Fax | E-post [info@direktronik.no](mailto:info@direktronik.no) | Org.nr 986767215MVA | Bankgiro 36285556559

## Structural return loss dB

MHz	dB
30 - 300	> 31
300 - 600	> 28
600 - 1000	> 27
1000 - 2000	> 24
2000 - 3000	> 22

## Screening effectiveness IEC 61196-1

MHz	dB
100 - 900	> 90
900 - 2000	> 80
2000 - 3000	> 70



**Direktronik AB** | Box 234, 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn  
 Telefon 08 52 400 700 | Fax | Epost info@direktronik.se | Org.nr 556281-9663 | Bankgiro 922-0179

SE



**NEXLAN AS** | Kokstadflaten 19 B, 5257 Kokstad | Besöksadresse Kokstadflaten 19 B 5257 Kokstad  
 Telefon 55 50 91 50 | Fax | E-post info@direktronik.no | Org.nr 986767215MVA | Bankgiro 36285556559

NO