

**20117367**

## RF 400 SHF1 - Solid

Low loss feeder cable

50Ω, double shielded

SHF1, UV, LSZH

Eq. LMR 400

DNV


### Application

Replaces RG-8/9913 as short run antenna feeder or jumper assemblies. Connects RF receiver systems with antenna systems in ships, buildings, tunnels and other underground installations. This product has better bending and handling properties, compared with cables with corrugated sheaths.



### Construction

Conductor	Solid Copper-clad Al 2.74 [mm]
Dielectricum	Cellular PE 7.25 ± 0.18 [mm]
Screen	Al - PET - AL Tape 100 [% optical coverage]
Screen	Tinned Cu-braid 90 [% optical coverage]
Jacket	Black SHF1
O.D.	10.3 ± 0.18 [mm]
Weight	124 ± 0.5 [kg/km]



### Specifications

Operating temperature normal	-40 – +80 [°C]
Test Voltage	6 [kV]
Characteristic impedance	50 ± 1.5 [Ω]
Braid Resistance	5 [Ω/km]
Conductor resistance	4.7 [Ω/km]
Capacitance	80 [pF/m]
Velocity factor	0,84
Min. bending radius	5 [x outer diam]
Min. bending radius flexible	10 [x outer diam]



SE




NO

**Direktronik AB** | Box 234, 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn  
Telefon 08 52 400 700 | Fax | Epost info@direktronik.se | Org.nr 556281-9663 | Bankgiro 922-0179

**NEXLAN AS** | Kokstadflaten 19 B, 5257 Kokstad | Besøksadresse Kokstadflaten 19 B 5257 Kokstad  
Telefon 55 50 91 50 | Fax | E-post info@direktronik.no | Org.nr 986767215MVA | Bankgiro 36285556559

## Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1 & IEC 60754-2
Material properties, insulation and sheath	IEC 60092-360 (359)
Design and testing standards	IEC 60096-0-1 Ed 3 IEC 61196-1-100
Flame resistance	IEC 60332-3-22
Flame retardant	IEC 60332-1-2
Smoke emission	IEC 61034-2
Oil and fuel resistant	IEC 60811-3-1
UV-resistant	UL 1581, ISO 4892
Euroclass	Eca
Certification	DNV



## Attenuation nominal, max 105%

Frequency MHz	Attenuation dB/100m
5	1.0
10	1.3
30	2.1
50	2.8
150	4.7
220	5.7
450	8.4
600	9.8
800	11.4
900	12.1
1000	12.8
1500	16.0
1800	17.7
2000	18.9
2500	21.1
3000	23.4
5200	32.7
5800	34.7



SE

**Direktronik AB** | Box 234, 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn  
Telefon 08 52 400 700 | Fax | Epost info@direktronik.se | Org.nr 556281-9663 | Bankgiro 922-0179



NO

**NEXLAN AS** | Kokstadflaten 19 B, 5257 Kokstad | Besöksadresse Kokstadflaten 19 B 5257 Kokstad  
Telefon 55 50 91 50 | Fax | E-post info@direktronik.no | Org.nr 986767215MVA | Bankgiro 36285556559

## Structural return loss

MHz	dB
30 – 450	< 27
450 – 1000	< 26
1000 – 2000	< 23
2000 – 3000	> 22
3000 – 4000	> 21
4000 – 5800	> 20

## Screen effectiveness IEC 61196-1

MHz	dB
100 – 900	> 95
900 – 2000	> 85
2000 – 3000	> 75



**Direktronik AB** | Box 234 , 149 23 Nynäshamn | Besöksadress Konsul Johnsons väg 15 149 45 Nynäshamn  
 Telefon 08 52 400 700 | Fax | Epost [info@direktronik.se](mailto:info@direktronik.se) | Org.nr 556281-9663 | Bankgiro 922-0179

SE



**NEXLAN AS** | Kokstadflaten 19 B, 5257 Kokstad | Besøksadresse Kokstadflaten 19 B 5257 Kokstad  
 Telefon 55 50 91 50 | Fax | E-post [info@direktronik.no](mailto:info@direktronik.no) | Org.nr 986767215MVA | Bankgiro 36285556559

NO