

# DIREKTRONIK

Dataprodukter utöver det vanliga



Floodlight without PIR



Floodlight with PIR

## Clarius™ Star

The **Clarius Star** is a high-quality LED floodlight designed for all outdoor lighting applications.

Modern aesthetics specifically designed to cater for the high-end residential and commercial markets and an adjustable bracket with the ability to pan and tilt help the **Clarius Star** stand out in the marketplace.

With a two year warranty and a 2500+ lumen output, it is the ideal replacement for older 250/300W halogen floodlights, as well as being environmentally friendly.

### Features include:

- Adjustable bracket to tilt and pan light
- Adjustable detection range between 4m to 12m, with 120° detection angle (Floodlight with PIR Sensor)
- Time on adjustable between 10 seconds and 10 minutes
- Pre-wired with high quality 1m cable
- Luxeon Cool white (5700k) LEDs
- Vandal-proof polycarbonate diffuser
- Average life expectancy of over 5 years
- IP65 rated

### PRODUCT CODES



**VCS-20** 20W Floodlight without PIR

**VCS-20-PIR** 20W Floodlight with PIR



	VCS-20	VCS-20-PIR
<b>DESCRIPTION</b>	LED Floodlight without PIR (20W)	LED Floodlight with PIR (20W)
<b>HOUSING COLOUR</b>	Black	Black
<b>LENS</b>	Frosted	Frosted
<b>LUMENS</b>	2500 +	2500 +
<b>VOLTAGE</b>	170-240VAC 50Hz	170-240VAC 50Hz
<b>IP RATING</b>	IP65	IP65
<b>ADJUSTABLE OUTPUT</b>	✓	✓
<b>DETECTION CIRCUIT</b>	N/A	Passive Infra-Red (PIR)
<b>PIR ANGLE</b>	N/A	120°
<b>PIR RANGE</b>	N/A	12m
<b>ACTIVATION TIME</b>	N/A	10 Secs - 10 Mins
<b>MOUNTING BRACKET</b>	✓	✓
<b>OVERRIDE OPTION</b>	✓	✓
<b>WEIGHT</b>	0.9Kg	0.9Kg
<b>DIMENSIONS</b>	241mm (w) x 61mm (H) x 153mm (D)	241mm (w) x 61mm (H) x 161mm (D)

# TECHNICAL SPECIFICATIONS

## 20W Floodlight without PIR



## 20W Floodlight with PIR



### GENERAL

**Electronics**  
**Construction**  
**Front Window**  
**Finish**  
**Power Cable**  
**Photocell**  
**Illumination**  
**Operating Temperature**  
**Weight**  
**Mount**  
**Dimensions**

High efficiency surface mount high power LUXEON LEDs  
 Robust high quality aluminium housing  
 Frosted polycarbonate high transmission  
 Black powder coat  
 1m  
 Adjustable 20 -70 Lux  
 Adjustable 10% - 100%  
 -30° to 50°C (-86° to 122°F)  
 0.9kg (1.9lbs)  
 Powder coated stainless steel wall mount  
 153 x 61 x 241mm (5.02" x 2.40" x 9.48")

### ELECTRICAL

**Input Voltage**  
**Consumption**  
**Power Factor**

170-240 VAC 50Hz  
 20W  
 0.9

### OUTPUT

**Lumen O/P**  
**Wavelength**  
**Colour Temp**  
**Colour Rendering Index**

2500+ lm  
 Visible (400-750nm)  
 5700K  
 70

### CERTIFICATIONS

#### WEEE

Waste Electrical & Electronic Equipment European Directive 202/96/EC

#### RoHS

Restriction Of Hazardous Substance European Directive 202/95/EC

#### CE-EMC

EN 61547  
 EN 55015  
 EN 62493  
 EN 61000

(Lighting-Immunity)  
 (Lighting-Emission)  
 (Lighting-EMF)  
 (EMC)

#### CE-LVD

EN 60598-1  
 EN 60598-2-1

(Luminaires-General)  
 (Luminaires)

#### Safety

EN 62471

(LED safety)



#### Environmental

IEC/EN 60529

IP65

N2580, EN 50581

(RoHS), REACH



Photometric files (.ies/.idt) available on request.



www.gjd.co.uk | info@gjd.co.uk | +44 (0) 1706 363 998

Unit 2 Birch Business Park, Whittle Lane, Greater Manchester, OL10 2SX