

1. Product Pictures



2. Features

5.0 megapixel HD 3G/4G IP camera, maximum resolution 2560x1920;

Support 3G/4G, support AP mode;

Support up to 128G TF card storage;

Support two way audio(built-in MIC and speakers);

Optional 2.8/3.6(default)/6mm lens;

Waterproof level IP66;

6pcs array infrared LEDs, night vision distance 25m;

Support P2P, view & anywhere & anytime;

Elegant outline and easy installation;

Provide android & ios APP and professional CMS PC client software;

3. Specifications

Model		20104017, 20104018
Video	Sensor	2.0 megapixel 1/2.8" SONY335 CMOS.
	Video resolution	Main stream: 2560x1920@15fps, 2560x1440@15fps Sub stream: 800x600/800x448@25fps, 640x480/640x352@25fps
	Video compression	H.265
	Lens	Optional 2.8/3.6(default)/6mm lens
	View angle	89.9°/75.7°(default)/50° based on lens
	Night vision	6pcs array infrared LEDs, night vision distance 25m
Audio	Audio compression	G.726/G.711
	Audio code rate	8Kbps, 16bit
	Audio input/output	Built-in MIC and speakers, support two way audio
Alarm	Motion detecting alarm	Can set 4 independent detection region (1-100 sensitivity can be set)
	Alarm linkage	Alarm send pictures to the mailbox, Alarm upload pictures and videos to the FTP server, Alarm record pictures and videos to Micro SD card, Alarm mobile phone message push, Alarm trigger sound alarm
	Alarm recording	Support Micro SD card and PC client linkage alarm recording
3G/4G	3G standard	WCDMA
	3G frequency range	B1(2100MHz), B8(900MHz)
	4G standard	FDD-LTE/TDD-LTE
	4G frequency range	B1(2100MHz), B3(1800MHz), B7(2600MHz), B8(900MHz), B20(800MHz), B38(2600MHz), B40(2300MHz), B41(2500MHz)
	Interface type	Nano SIM card, Plug and play, no need to set
Storage	Micro SD card	Support up to 128G micro SD card
	Recording mode	Alarm record, timing record,
	Video playback	Support APP, IE browser, remote client play and download the video
General specification	Power	DC12V 1A
	Operating environment	Environment -20°C~+60°C(-4°F~+140°F), Humidity 10%~90%, non-condensing
	Shell material	All metal shell
	Waterproof level	IP66
	Product size	175mm×62mm×66mm(L×W×H)

	Product weight	0.35kg
	Package size	218mmx158mmx106mm(L×W×H)
	Package weight	0.6kg
	Reset button	Support