

Product Features

- Hybrid optical cable with fiber and copper wire
- Accord with HDMI 2.0 standard , backward compatible with HDMI1.4
- Supports computer resolutions to 1080P and 4K2K(60P)
- Support HDCP2.2/1.4
- Support (HDR) Dynamic HDR formats
- Support self-detecting function for EDID information
- No loss of signal – delivering crystal clear digital images instantly
- Plug and Play , no external power required
- Up to 30m Maximum Length.(Custom Length Available)
- OD4.5mm super slim stainless steel construction


Applications

- Digital Signage, LED signboards in streets and in stadiums
- Medical Imaging Equipment
- Airplane On-board Video System
- Home Theater, conference Room Video Equipment
- Blue-ray, 3D video, Projector, Set-up box, DVR, Game Consoles and Computer
- TV Broadcast Station
- Conference Room Video Equipment
- Security systems


Operating Condition

Parameter	Unit	Min.	Typical	Max.
Storage Temperature	°C	-40	25	80
Operating Temperature	°C	-20		50
Power Supply Voltage	V	4.5	5	5.5
Power Consumption	mW			250
Bandwidth	Gbps			18
Operating Current	mA		45	120


Typical Interface Circuit



PIN Definition



Finished product drawings



Version number

Version	Date	Description
V001	2024-05-28	New release