
THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NO.	BUNDLE DIA. MIN. (mm) MAX. (mm)		A in (mm)	B in (mm)	C in (mm)	MIN. LOOP* TENSILE lbs.	PACKAGE DESCRIPTION
HLB2S-C	.25	1.6	.100 (2.5)	7.0 (178)	.750 (19.1)	50 (222)	100 PIECES STACKED 5 ACROSS 20 ROWS HIGH (STAGGERED)



NOTES:

- 1) TIES ARE STACK-PACKED (SEE ILLUSTRATION 'A')
- * 2) MINIMUM 2" OVERLAP REQUIRED TO ACHIEVE LOOP TENSILE RATING.
 - 3) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR OPTIONAL COLORS.

ILLUSTRATION 'A'

								DIMENSIONS IN PARENTHESIS ARE IN METRIC UNITS						
												W10001CM/C	01	
											VUUI corp.	RP. TINLEY PARK, ILLINOIS		
										TAK-TY HOOK & LOOP CABLE TIES HLB SERIES				
										UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± .035 (.XX) ± ANGLES ±		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJEC	CTION.	
01	01-14-19	SAT	DWW	B. UPDATED MATERIAL. A. REMOVED APPROXIMATE WEIGHT COLUMN.	27571	01				DRAWN BY ERW	MAT'L:	scale NONE		
R	1/7/08	ERW		DRAWING RELEASED	27571	R				1/7/08	BACK-TO-BACK HOOK & LOOP HOOKS: POLYETHYLENE OR NYLON ^	DRAWING NO.	DWG	
REV	DATE	BY	СНК	DESCRIPTION	ECN -	R	CUST	SUP		CHK'D	LOOPS: NYLON	SS-27571	SIZE	