

Isolerade TWIN-ändhylsor 2 x 0,5 - 16 mm²

■ Data: Cu, förtent, nylon (PA), färgkod W, avsedd för 2 parallella ledare.

	Area område, mm ²	Best nr	mm L	L ₁	d	D	H	s	St/pack
	2x0,5	KA0,5-8ETW2	15	8	1,5	4,7	2,5	10	500
	2x0,75	KA0,75-8ETW2	15	8	1,8	5,0	2,8	10	500
	2x1	KA1-8ETW2	15	8	2,05	5,4	3,4	10	500
		KA1-10ETW2	17	10	2,05	5,4	3,4	12	500
	2x1,5	KA1,5-8ETW2	16	8	2,3	6,6	3,6	10	500
		KA1,5-10ETW2	20	12	2,3	6,6	3,6	14	500
	2x2,5	KA2,5-10ETW2	18,5	10	2,8	7,8	4,2	12	500
		KA2,5-13ETW2	21,5	13	2,8	7,8	4,2	15	500
	2x4	KA4-12ETW2	23	12	3,7	8,8	4,9	14	500
	2x6	KA6-14ETW2	26	14	4,8	10,0	6,9	16	500
	2x10	KA10-14ETW2	26,5	14	6,4	12,8	7,6	16	100
	2x16	KA16-14ETW2	31,5	14	8,3	18,6	9,6	16	100

s = avisoleringslängd

